



Document Solutions

> PRINT

ECOSYS P2135dn

MONOCHROME DESKTOP PRINTER
FOR A4 FORMAT

THE HIGH PERFORMANCE DESKTOP PRINTER



Fast and efficient, the ECOSYS P2135dn is the ideal printer for small teams. Featuring standard network connectivity, automatic duplex, clarity of the LCD control panel for user-friendliness, and fast 35 pages per minute A4, the ECOSYS P2135dn easily handles larger print volumes. With its strong productivity and low total cost of ownership thanks to Kyocera's ECOSYS® long-life technology, the ECOSYS P2135dn is the desktop printer you can count on.

- › Up to 35 pages per minute in A4
- › Fine 1,200 dpi printing quality
- › Standard duplex functionality for double-sided printing
- › Standard USB and Network Connectivity
- › 250-sheet universal paper cassette
- › 50-sheet multi-purpose tray
- › Easy to read LCD Operation Panel
- › Exceptionally low printing costs in its class



stands for ECOlogy, ECONomy and SYStem-printing. With long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly, and the drum units every 300,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

PRESCRIBE IIc

With the Kyocera page design and control language PRESCRIBE IIc, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

GENERAL

Technology: Kyocera ECOSYS Laser Printer

Operating systems: All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX, LINUX as well as other operating systems on request

Engine speed: Up to 35 pages per minute in A4

Resolution: Fine 1,200 dpi

Duty cycle: Max. 50,000 pages per month

Warm-up time: Approx. 16.5 seconds or less from power on

Time to first page: Approx. 8 seconds or less

Dimensions (W x D x H): 375 mm x 393 mm x 267 mm

Weight: Approx. 12 kg (main unit)

Power source: 220/240 V, 50/60 Hz

Power consumption:

Printing: 499 W

Stand-by: 11 W

Sleep: 2.5 W

Safety standards:

GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

CPU: PowerPC 465 S / 500 MHz

Memory: Standard: 256MB RAM
Maximum: 1,280MB RAM

Standard interface: Gigabit Ethernet: 10/100/1000Base-TX, USB 2.0 (Hi-Speed), eKUIO slot for optional NIC, SD/SDHC slot for API/optional fonts (Max 32GB)

PAPER HANDLING

All paper capacities quoted are based on 80gsm paper, thickness of 0.11mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray; 60–220 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 – 215.9 x 356 mm)

250-sheet universal paper cassette, 60–120 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 215.9 x 297 mm)

Max. paper capacity incl. options: 800 sheets A4

Duplex unit: Double-sided printing standard supports: 60–105g/m²; A4, A5, B5, Letter, Legal, Custom (140 x 210 - 215.9 x 297mm)

Output capacity: 250 sheets face-down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc

Emulations: PCL6/PCL5e incl. PjL, KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF Direct Print v1.7, XPS

Fonts/Barcodes: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

The KYOCERA NetViewer

The KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital Kyocera multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Centre

The Status Monitor shows the current printers condition and gives direct access to the Command Centre for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

OPTIONS

PF-100 Paper feeder (max. 2 units):

Max. 250 sheets; 60–120 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 215.9 x 297 mm)

Max. 2 x PF-100 can be attached for a total of 800 sheet input

Memory Upgrade:

DIMM-512P: 512MB

DIMM-1GBP: 1,024MB

1 slot available for memory upgrade

CompactFlash® card:

1 slot (up to 32GB) for printing forms, fonts, logos, macro storage

Optional interface:

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT

IB-51: Wireless LAN (802.11b/g/n)

CONSUMABLES

TK-174 Toner-Kit: Microfine toner for 7,200 pages A4, at 5% coverage, in accordance with ISO/IEC 19752
Capacity of starter toner is 2,300 pages A4, at 5% coverage, in accordance with ISO/IEC 19752

MK-174 Maintenance Kit: Installed at 100,000 pages



KYOCERA Document Solutions Australia
Ph: 13 KYOCERA (596 2372)
www.KyoceraDocumentSolutions.com.au

KYOCERA Document Solutions New Zealand*
Ph: 0508 KYOCERA (596 2372)
www.KyoceraDocumentSolutions.co.nz

* KYOCERA Document Solutions New Zealand is the trading name of the New Zealand branch of KYOCERA Document Solutions Australia Pty Ltd a corporation incorporated in Australia.

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.